



## Automatic Transfer Switch (ATS) PDU Series

### Features

- 19 inch rack-mount style ATS PDU
- Dual power supply for redundancy
- Seamlessly transfer between two power sources
- A / B power source (selectable)
- MCU embedded technology
- Total load-current and input / output voltage monitoring
- SNMP module for remote management (optional)



ATS - 1508 / 1608E (front without SNMP module)



ATS-1508S / 1608ES (front with SNMP module)



ATS-1508 / 1508S (LV rear)



ATS-1608E / 1608ES (HV rear)



ATS-3016 / 3216E (front without SNMP module)



ATS-3016S / 3216ES (front with SNMP module)



ATS-3016 / 3016S (LV rear)



ATS-3216E / 3216ES (HV rear)

### ATS PDU SPECIFICATION

MODEL	ATS - 1508 (S)	ATS - 3016 (S)	ATS - 1608E (S)	ATS - 3216E (S)
<b>INPUT</b>				
Voltage	110 / 120 VAC (LV)		220 / 230 / 240 VAC (HV)	
Frequency	50 Hz or 60 Hz			
Plug Type	NEMA 5-15P	NEMA L5-30P	IEC320 C20	IEC60309 32A
Load Current	15 A	30 A	16 A	32 A
<b>OUTPUT</b>				
Socket Type & Quantity	NEMA 5-15R x 8	NEMA 5-15R x 12 NEMA 5-15 / 20R x 4	IEC320 C13 x 6 IEC320 C19 x 2	IEC320 C13 x 12 IEC320 C19 x 4
Total Current	15 A	30 A	16 A	32 A
Transfer Polarity	yes			
Transfer Time	10 ms (typical)			
<b>DISPLAY</b>				
Indicators	Output current, output voltage, A / B source indicator, Primary source indicator, present source indicator			
<b>PROTECTION</b>				
Overload Protection	yes			
<b>ALARM</b>				
Logical Port	yes			
<b>COMMUNICATION</b>				
Serial Port	yes			
SNMP Module (Optional)	Remote management via network (for S model)			
<b>PHYSICAL</b>				
Dimensions (L x W x H) (mm / in)	482.6 x 220 x 44.4 (1U) / 188.2 x 85.8 x 17.3 (1U)	482.6 x 220 x 88.8 (2U) / 188.2 x 85.8 x 34.6 (2U)	482.6 x 220 x 44.4 (1U) / 188.2 x 85.8 x 17.3 (1U)	482.6 x 220 x 88.8 (2U) / 188.2 x 85.8 x 34.6 (2U)
Mounting Length (mm / in)	465.0 / 181.3 (both sides installation with brackets)			
<b>ENVIRONMENT</b>				
Operating Environment	0 ~ 45°C, 0 ~ 95% relative humidity (non-condensing)			