



NET-1000TW/1500TW

NET-500TW/750TW

POWERNET SERIES FEATURES

- Ideal for network equipment, NAS, ATM, and Kiosks
- Line-interactive UPS with sine wave output
- Cost-efficient solution without compromising the performance
- High conversion efficiency (>95%) results in energy saving
- Automatic boost and buck voltage regulation
- LCD graphic display gives comprehensive information at a glance
- Rapid charge allows the batteries to reach 90% in 3 hours
- Compact design and easy to install
- Auto restart while AC is recovering
- Easy battery replacement



APPLICATIONS

- Midsize Servers
- Telecom & Networking
- ATM Machines
- Slot Machine



POWERNET LINE INTERACTIVE UPS SPECIFICATION

MODEL	NET-500TW	NET-750TW	NET-1000TW	NET-1500TW
CAPACITY	500VA/350W	750VA/450W	1000VA/700W	1500VA/900W
INPUT				
Voltage	100/110/120 or 220/230/240VAC			
Voltage Range	96-144VAC or 184-276VAC			
Nominal Frequency	50 or 60Hz (auto sensing)			
OUTPUT				
Voltage	100/110/120 or 220/230/240VAC			
Regulation	-10% to +6%			
Frequency	50 or 60Hz (auto sensing)			
Transfer Time	2~6ms typical			
Waveform	Pure sine wave			
BATTERY				
Battery Type & Quantity	12V/7Ah x 1	12V/9Ah x 1	12V/7Ah x 2	12V/9Ah x 2
Backup Time (Typical PC Load)	17 minutes	20 minutes	35 minutes	40 minutes
Recharge Time	3 hours to 90%			
COMMUNICATION				
USB Interface	For Windows 2003/2008/XP/Vista/7/8			
PHYSICAL				
Dimension (D x W x H) (mm/in)	240 x 150 x 209 / 9.4 x 5.9 x 8.2		340 x 150 x 209 / 13.3 x 5.9 x 8.2	
Net Weight (kg/lb)	6.4/14.1	6.8/15.0	10.8/23.8	11.5/25.3

* Product specifications are subject to change without further notice