

**PRO AVR FEATURES**

- 1200~2000VA AVR
- 8 outlets (4 AVR + surge & 4 surge only) for 1200VA / 2000VA
- Desktop and wall-mountable design
- RJ-11 / 45 telephone / fax / internet data line surge protection
- Resettable input overload protection circuit breaker
- Automatically regulates high and low voltage
- User-friendly visual indicators
- Overheating protection



AVR-1200AC / 2000AC

**MICRO AVR FEATURES**

- Input voltage and output voltage LCD display
- 8 outlets for 3000VA~5000VA
- Two-boost and buck AVR to stabilize input voltage
- Resettable circuit breaker for overload protection
- Selectable delay time setting (2 / 10 / 30 seconds)
- RJ-11 / 45 combo telephone / fax / network line protection port
- High voltage & Low voltage protection
- Overheating protection



AVR-3000 / 4000 / 5000LCD

**APPLICATIONS**

- Home Entertainment Systems
- Network Peripherals
- Personal Computers
- Printers & Copiers

**APPLICATIONS**

- Home Appliances
- Office Equipment
- Personal Computers
- Factory Automation

**PRO & MICRO AVR SPECIFICATION**

SERIES	PRO AVR		MICRO AVR		
	AVR-1200AC	AVR-2000AC	AVR-3000LCD	AVR-4000LCD	AVR-5000LCD
Capacity	1200VA / 600W	2000VA / 1000W	3000VA / 1500W	4000VA / 2000W	5000VA / 2500W
<b>AC INPUT</b>					
Nominal Voltage	120 / 230VAC		120 / 220VAC		
Input Voltage Range	95~150VAC / 176~278VAC		85~145VAC / 175~290VAC		
Phase	1 phase 2 wires				
Frequency	50 / 60Hz (auto sensing)				
<b>AC OUTPUT</b>					
Nominal Voltage	120 / 230VAC		120 / 220VAC		
Output Voltage Range	±10%		±10%		
Phase	1 phase 2 wires				
Frequency	50 / 60Hz				
<b>OUTLETS</b>					
Surge only	4 PCS		N / A		
AVR + Surge Protection	4 PCS		8 PCS		
<b>PROTECTION</b>					
Surge Suppression	110 Joules		240 Joules		
Network Surge Suppression	RJ-11 / RJ-45				
Overload	Manual reset circuit switch				
Over Current	Manual reset circuit switch				
Short Circuit	Manual reset circuit switch				
<b>PHYSICAL</b>					
Dimension (D x W x H) (mm / in)	80 x 95 x 250 / 3.15 x 3.74 x 9.84		250 x 150 x 157 / 9.8 x 5.9 x 6.2		
Net Weight (kg / lb)	1.4 / 3.1	2.3 / 5.1	5 / 11	6 / 13.2	7 / 15.4

Product specifications are subject to change without further notice.