

RAIL DC UPS FEATURES

- Universal full range 90~264V AC input
- Cooling by free air convection
- Can be installed on DIN rail
- Overload and short circuit protection
- Battery low and battery reverse polarity protection
- Terminal block AC input and DC output ports
- DC voltage output adjustment knob
- LED indicator for power on



RAL-40W12V / 40W24V

UNIQUE DC UPS FEATURES

- Universal full range 90~264V AC input
- Horizontal / vertical / wall-mountable design
- DC cold start function
- Dry contact communication interface
- Overload and short circuit protection
- Over temperature and battery low protection
- Overvoltage and overcurrent protection
- LEDs display status and alarm information



UNI-40W12V / 60W12V

APPLICATIONS

- Security Systems
- Access Systems
- Emergency Lighting
- Central Monitoring Systems

APPLICATIONS

- Surveillance Devices
- VoIP / VoDSL
- Emergency Lighting
- Router / Digital Camera

RAIL & UNIQUE DC UPS SPECIFICATION

SERIES	RAIL DC UPS		UNIQUE DC UPS	
MODEL	RAL-40W12V	RAL-40W24V	UNI-40W12V	UNI-60W12V
Capacity (Total)	40 W			60 W
INPUT				
Voltage	90 ~ 264 VAC			
Frequency	50 / 60 Hz			
DC OUTPUT				
Output Voltage	13.8 VDC	27.6 VDC	13.5 VDC	
Output Capacity	26.2 W		40 W	60 W
CHARGING OUTPUT				
Output Voltage	13.8 VDC	27.6 VDC	N / A	
Output Capacity	13.8 W			
BATTERY				
Battery Type	Supports lead acid battery			
Capacity	N / A		5.0 Ah	7.0 Ah
Battery Voltage	12 VDC	24 VDC	12 VDC	
Charging Voltage	13.8 VDC	27.6 VDC	13.5 VDC	
INDICATOR				
Display	Work status		Work status; battery status; auxiliary power	
PROTECTION				
Overcharge / Over Discharge	Yes			
Overload / Short Circuit	Yes			
PHYSICAL				
Dimension (D x W x H) (mm / in)	89.5 x 30 x 75 / 3.5 x 1.2 x 3.0		78 x 216.5 x 181 / 3.1 x 8.5 x 7.1	
Net Weight (kg / lb)	0.25 / 0.55		2.35 / 5.2	2.75 / 6.1

Product specifications are subject to change without further notice.