



PRO-1000LCD /
1500LCD / 2000LCD

PRO-550LCD / 800LCD

POWERPRO SERIES FEATURES

- 550VA ~ 2000VA line interactive UPS
- LCD display for more reliable power status feedback
- Advance battery management, increases longevity, performance, and reliability
- Two-boost and one-buck AVR to stabilize input voltage
- Auto restart while AC is recovering
- Off-mode charging
- HID USB communications interface with power management software
- RJ-11 / 45 combo telephone / fax / network line protection port



APPLICATIONS

- Desktop PCs
- P.O.S. & Surveillance
- Small Server
- Gaming Computer



POWERPRO LINE INTERACTIVE UPS SPECIFICATION

MODEL	PRO-550LCD	PRO-800LCD	PRO-1000LCD	PRO-1500LCD	PRO-2000LCD
Capacity	550VA / 300W	800VA / 450W	1000VA / 600W	1500VA / 900W	2000VA / 1200W
INPUT					
Voltage	110-120 VAC				
Voltage Range	82-148 VAC				
Frequency Range	60 Hz / 50 Hz (Auto Sensing)				
OUTPUT					
Output Voltage	110-120 VAC				
Frequency Range (Batt. Mode)	60 Hz / 50 Hz ± 1%				
Transfer Time	4ms (typical)				
Overload Protection	Circuit breaker				
Waveform (Batt. Mode)	Simulated Sinewave				
Outlets	6 Outlets (3 battery backup + surge & 3 surge only)		8 Outlets (4 battery backup + surge & 4 surge only)		
BATTERY					
Battery Type & Quantity	12 V / 7 Ah x 1	12 V / 7.2 Ah x 1	12 V / 7 Ah x 2	12 V / 7.2 Ah x 2	12 V / 9 Ah x 2
Charging Current	1A				
Backup Time (Basic PC)	Up to 43 minutes	Up to 48 minutes	Up to 78 minutes	Up to 88 minutes	Up to 116 minutes
Recharge Time	4 hours charge to 90%				
PROTECTION					
Full Protection	Overcharge and overload protection				
Phone / Fax / DSL / Network Surge Protection	RJ-11 / 45				
EMI / RFI Filter	Full time				
AC Surge Protection	Full time, 735 joules				
COMMUNICATION					
USB Interface	Windows® 10 / 8 / 7 / Server 2012 R2 / Server 2008 R2 / Linux / Mac				
PHYSICAL					
Dimension (D x W x H) (mm / in)	286 x 96 x 138 / 11.3 x 3.8 x 5.4		298 x 148 x 178 / 11.7 x 5.8 x 7.0		
Net Weight (kg / lb)	4.35 / 9.6	5.08 / 11.2	8.66 / 19.1	10.65 / 23.5	11.36 / 25.0